# **Operational Excellence** Instructions for the safe use of:

# Subsea Baskets



#### The information in this leaflet should be passed to the user of the equipment

This document is issued in accordance with the requirements of DNV GL 2.7-3. It outlines the care and safe use of SUBSEA BASKETS and is based on the Oil & Gas UK "Best Practice for the Safe Packing & Handling of Cargo to & from Offshore Locations". It should be read in conjunction with the instructions for the safe use of Wire Rope Slings.

This information is of a general nature only covering the main points for the safe use of SUBSEA BASKETS. It may be necessary to supplement this information for specific operations.

## ALWAYS

Ensure operators wear appropriate personal protective equipment (PPE) e.g. gloves, hard hat, safety glasses, and safety footwear.

Ensure operators are trained and competent.

Ensure dangerous goods are shipped incompliance with the requirements of the IMDG Code.

### NEVER

Use equipment without carrying out a pre-use inspection.

Use equipment that has not been periodically inspected and certified.

Replace lifting sets without the approval of a competent person.

Use equipment out with its intended purpose.

### **Pre-use Inspection**

Ensure hatches function correctly with hinges and locking gear free moving and undamaged.

Ensure loading ramps function correctly with hinge bolts and locking mechanism free moving and undamaged.

Ensure securing devices (bar or ratchet) function correctly with hinges, cams, pins, etc., free moving and undamaged.

Ensure tie down points are in place and fit for purpose.

Ensure the data plate is legible and demonstrates sufficient certification.

Ensure the safety, identification, and information markings are clear and leaible.

Ensure the lifting set is correctly fitted with shackles and split pins fully engaged.

Ensure the lifting set is free of obvious signs of damage, e.g. abrasion, corrosion, wear, chemical attack, and mechanical damage.

## Loading & Operation

Ensure the load is equally distributed and does not exceed the payload of the unit.

Ensure the load is safely secured using the provided lashing point(s).

Ensure hatches and/or loading ramps are always secured via the locking mechanism when in the OPEN or CLOSED position.

## Movement & Transport

Ensure all signs and placards are in place and incompliance with the IMDG Code.

Ensure roof, forklift pockets, frame, etc., is free of potential dropped obiects.

Ensure the total consignment weight does not exceed the maximum gross weight of the unit.

Ensure all lifting is performed with carried out through the forklift pockets or dedicated lifting set.

Lifting must be carried out by competent persons in accordance with an appropriate lifting plan.

## Maintenance & Inspection

Moving parts such as hinges, locking gear, shackles, etc., must be regularly lubricated to ensure free movement and prevent corrosion.

Grating fastening must be regularly checked and re-torqued accordingly.

Paintwork damage must be regularly treated to prevent corrosion.

Anodes must be regularly checked and replaced accordingly.

Lifting sets shall be subjected to as a minimum:

- Thorough examination at intervals not exceeding 12 months. •
- Non-destructive examination, and visual examination of components and joining links at intervals not exceeding 48 months.
- Non-destructive examination, and visual examination of chain sling legs at intervals not exceeding 48 months

Subsea Baskets shall be subjected to as a minimum:

- Visual examination at intervals not exceeding 12 months.
- Non-destructive examination, and visual examination at intervals not exceeding 48 months.
- Proof load test, non-destructive examination, and visual examination after substantial repair or alteration.

| SWIRE | OILFIELD | SERV | ICES |
|-------|----------|------|------|
|       |          |      |      |

| 5 | Document Ref.   | SUI-22           |
|---|-----------------|------------------|
|   | Document Owner. | Group Operations |
|   | Revision.       | -                |
|   |                 |                  |

© Copyright 2019 Swire Oilfield Services Ltd. All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

RELIABLY DYNAMIC

# **Operational Excellence**

Instructions for the safe use of:

## Subsea Baskets

ORTANT SAFET TO MFORM

The information in this leaflet should be passed to the user of the equipment

## Subsea Basket



Note. Design may not be wholly representative of the actual subsea basket.



© Copyright 2019 Swire Oilfield Services Ltd. All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.